



120 TDBK

Cassetti interni estraibili
Internal removable drawers

Chiave a Doppia Mappa

- Alta protezione contro il fuoco: resistenza di 120 min. data e 120 min. diskette in condizioni di esposizione al fuoco ad una temperatura di 1010°C.
- Serratura ad alta sicurezza testata EN 1300 con chiave femmina a doppia mappa.
- Cassa interna supplementare costituita da pannelli di materiale melaminico e da specifiche protezioni che hanno funzione di isolante termico.
- Le guarnizioni della cassa interna e le scanalature della porta esterna assicurano la tenuta ermetica a liquidi, aria, vapore e fumo.
- Protezione contro i campi magnetici ed i fenomeni elettrostatici.
- **Cassetti estraibili su guide telescopiche provvisti di divisori interni regolabili.**
- Ripiani interni regolabili.
- Ruote e profili copriuote.

Double-Bitted Key

- High fire protection: 120 min data and 120 min. diskette fire resistance, depending on the models, at a constant temperature of 1010°C.
- Lock controlled by a high security lock with double-bitted key, EN 1300 certified.
- Additional internal box, made of melamine panels and heat insulating materials.
- The gaskets on the internal box and the grooves on the external door ensure a hermetic seal against liquids, air, gas, steam and smoke.
- Protection against magnetic fields and electrostatic phenomena.
- **Adjustable sliding drawers with internal removable divisors.**
- Internal removable shelves.
- Equipped with wheels and metal wheel covers.



Art	Misure esterne mm.			Misure interne mm.			Resistenza al fuoco	Ripiani	Cassetti	Peso	Litri
Code	External dim. mm.			Internal dim. mm.			Fire Resistance	Shelves	Drawer	Weight	Volume
	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Minuti/Min	N°	N°	Kg	Lt
825 TDBK	830	690	720	489	402	406	120 - data/dis	1	2	264	80
120 TDBK	1220	690	720	879	402	406	120 - data/dis	1	4	352	143
130 TDBK	1445	690	720	1104	402	406	120 - data/dis	1	5	479	180
635 TDBK*	1745	1200	720	1404	402x2	406	120 - data/dis	4	10	765	450

Art	Capacità interna (solo cassetti)						
Code	Internal Capacity (only drawers)						
	4mm DAT	8mm AIT	CD	DLT	LTO/Ultrium	LTO/Ultrium (without case)	3590 Cartridge (without case)
825 TDBK	232	114	188	84	88	114	96
120 TDBK	464	228	376	168	176	228	192
130 TDBK	580	285	470	225	220	285	240
635 TDBK*	1160	570	940	420	440	570	480

* Versione con 2 ante

* Version with double door